
FLX-DM2





TECHNICAL DATA

Max. height fall Dimensions (W x L x H) Safety area dimensions Safety area Recommended surface

1,4 m 2,36 x 1,00 x 1,40 m 5,4 x 4,0 m 19,5 m² According to norm 1176-1:2017

Available options:

	PREMIUM	PREMIUM PLUS
STEEL	Galvanized and powder coated steel elements	Structural poles of stainless steel, other elements made of galvanized steel with powder coating **
PLATES	HDPE / HPL and HDPE plastic panels with three layers and milled drawings	HDPE / HPL and HDPE plastic panels with three layers and milled drawings.
FOUNDATIONS	The device permanently sited in the ground with C16 / 20 class concrete	The device permanently sited in the ground with C16 / 20 class concrete
ADDITIONAL ELEMENTS	Structural beams covered with steel lids welded to poles. The heads of the screws and nuts covered with plastic plugs. Cap nuts	Structural beams covered with steel lids welded to poles. The heads of the screws and nuts covered with plastic plugs. Cap nuts

* Due to the continuous improvement of technical solutions by FreeKids, presented drawings, including colors and dimensions may slightly differ from currently manufactured devices. Certificate of compliance with the PN-EN 1176: 2017 ** Optional execution of stainless steel elements (valuation available on individual request).



